

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<p>(51) International Patent Classification <sup>6</sup> : <b>A61F 5/445</b></p>	<p><b>A1</b></p>	<p>(11) International Publication Number: <b>WO 96/37171</b> (43) International Publication Date: 28 November 1996 (28.11.96)</p>
<p>(21) International Application Number: PCT/GB96/01267 (22) International Filing Date: 24 May 1996 (24.05.96) (30) Priority Data: 9510596.1 25 May 1995 (25.05.95) GB 9601690.2 27 January 1996 (27.01.96) GB (71) Applicant (for all designated States except US): ECO-PROGRESS LIMITED [GB/GB]; St John's Innovation Centre, Cowley Road, Cambridge CB4 4WS (GB). (72) Inventors; and (75) Inventors/Applicants (for US only): BROWN, Malcolm, David [GB/GB]; 10 The Lammas, Mundford, Norfolk IP26 5DT (GB). MUNCASTER, Barry, John [GB/GB]; Ecoprogress Limited, St John's Innovation Centre, Cowley Road, Cambridge CB4 4WS (GB). (74) Agent: JONES, William; William Jones, Willow Lane House, Willow Lane, Norwich, Norfolk NR2 1EU (GB).</p>		<p>(81) Designated States: AL, AM, AT, AU, AZ, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IS, JP, KE, KG, KP, KR, KZ, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, US, UZ, VN, ARIPO patent (KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).</p> <p><b>Published</b> <i>With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i></p>
<p>(54) Title: A WATER-DISPERSIBLE DISPOSABLE ENCLOSURE</p> <p>(57) Abstract</p> <p>A water-dispersible disposable enclosure, such as an ostomy pouch or urinary incontinence pouch, which is adapted for flushing down the bowl of a water closet and is formed of a material that is, at least at the time of disposal into a water closet bowl, combined with a water-activated exothermic reagent that raises the temperature of the enclosure or the water that comes into contact with the enclosure, prior to or upon placement in the water closet bowl, to a level at which the material melts, dissolves or otherwise disperses for ease of flushing.</p> <div data-bbox="893 1197 1266 1680"><p>The diagram shows a cross-sectional view of a water-dispersible disposable enclosure. It is an elongated, rounded rectangular shape with a textured, stippled surface. At the top, there is a circular opening (1) surrounded by a thicker, possibly reinforced, ring. A label (3) is attached to the top edge of the enclosure. The main body of the enclosure is labeled (2).</p></div>		

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IE	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgyzstan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic of Korea	SD	Sudan
CF	Central African Republic	KR	Republic of Korea	SE	Sweden
CG	Congo	KZ	Kazakhstan	SG	Singapore
CH	Switzerland	LJ	Liechtenstein	SI	Slovenia
CI	Côte d'Ivoire	LK	Sri Lanka	SK	Slovakia
CM	Cameroon	LR	Liberia	SN	Senegal
CN	China	LT	Lithuania	SZ	Swaziland
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	LV	Latvia	TG	Togo
DE	Germany	MC	Monaco	TJ	Tajikistan
DK	Denmark	MD	Republic of Moldova	TT	Trinidad and Tobago
EE	Estonia	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	UG	Uganda
FI	Finland	MN	Mongolia	US	United States of America
FR	France	MR	Mauritania	UZ	Uzbekistan
GA	Gabon			VN	Viet Nam

## A WATER-DISPERSIBLE DISPOSABLE ENCLOSURE

### Field Of The Invention

5 The present invention relates to the field of water-dispersible disposable health care goods and particularly but not exclusively to ostomy and faecal and urinary incontinence pouches.

### Background to the Invention

10 There are a surprisingly large number of patients, most notably in the UK and USA, who have undergone major surgery of the digestive track and are reliant upon a colostomy or ileostomy pouch to collect unabsorbed or excreted waste material from the digestive tract. For such patients use of these pouches represents a very considerable hardship and invariably involves wearing the pouch for many hours on end and awkward fitment and removal at frequent intervals with the further problem that upon removal of the pouch it must then be disposed of.

15 Fitment and removal of an ostomy pouch is generally carried out within the confines of a water closet and the pouch then is either emptied of its contents into the water closet bowl with the pouch then being binned or sealed away for carriage to a remote waste disposal unit or the pouch is adapted to be flushed away, following emptying or complete with its contents.

20

A variety of different designs of ostomy bag exist that are adapted for flushing and which are, for example, either adapted to be softened in the cold water of the toilet bowl or dispersed in hot water such as arises in the sludge digester of a sewage treatment plant and as disclosed in, for example, GB 2 290 968.

- 5 For those designs that are adapted to disperse or biodegrade in the environment of a sludge digester this does not, of course, facilitate the flushing of the product or its transit through the soil pipe and sewage drains. Other product designs are adapted to disperse upon contact with cold water when the pH of that water is adjusted to a level at which the material of the pouch is cold water
- 10 soluble. Examples of the latter include US 5,417,677 and GB 2 195 919. Such prior art systems of flushing disposal of ostomy and incontinence pouches are, however, not necessarily swift methods of disposal or do not allow for complete dispersal prior to flushing or, furthermore, require the carrying of potentially dangerous acid or alkali by the patient/wearer.
- 15 It is a general objective of the present invention to provide an ostomy/incontinence pouch or bag that is rapidly dispersible for flushing down a water closet without necessitating carrying of acidic or alkaline substances to facilitate the dispersion.

#### Summary of the Invention

- 20 According to a first aspect of the present invention there is provided a water-dispersible disposable enclosure such as an ostomy pouch or urinary incontinence pouch which is adapted for flushing down the bowl of a water closet and is formed of a material that at the time of disposal into a water closet bowl is combined with a water-activated exothermic reagent that raises the
- 25 temperature of the enclosure or the water that comes into contact with the enclosure, prior to or upon placement in the water closet bowl, to a level at which the material melts, dissolves or otherwise disperses for ease of flushing.

- The preferred material of the enclosure is a hot water soluble material such as hot water soluble polyvinyl alcohol and the preferred water-activated exothermic
- 30 reagent is silica gel, aluminium chloride or calcium chloride. Each of these

water-activated exothermic reagents is capable of raising the localised temperature of the aqueous media within the enclosure or the immediately surrounding water to a level of 60°C or 80°C necessary to dissolve or disperse the hot water soluble polyvinyl alcohol from which the enclosure is formed or to heat and melt an enclosure formed of low melting point material such as 60°C MP polycaprolactone film.

It will be appreciated that the material forming the enclosure is not soluble, dispersible or meltable at body temperature and is, therefore, not vulnerable to degradation by the warm bodily liquids that it is adapted to store. Therefore, by provision of the water-activated exothermic reagent only upon the external surface of the enclosure the enclosure is vulnerable only to externally applied water/aqueous media. Alternatively, by introducing the exothermic reagent into the enclosure only at time of disposal it retains its integrity until disposal.

The water-activated exothermic reagent may be coated upon the external surface of the enclosure at the time of manufacture and may be applied continuously or discontinuously as necessary to achieve adequate disintegration of the product upon disposal. For the greater comfort of the user, depending upon the nature of reagent used, the reagent may be best applied substantially solely to the face of the pouch/enclosure that is remote from the wearer, rather than adjacent the skin of the wearer.

The water-activated exothermic reagent may be applied at the time of disposal by means of a spray, wipe or applicator pen or may be incorporated in or on the enclosure, for example inside a sachet which is punctured or ruptured by the action of a tool or force after the useful life of the enclosure or within a pocket on the enclosure that is cold water soluble to release the reagent upon placement in the bowl of the water closet, or may be introduced into the enclosure through a valve.

According to a second aspect of the present invention there is provided a water-dispersible disposable enclosure such as an ostomy pouch or urinary incontinence pouch, which enclosure is formed from a material that is rapidly soluble in an organic solvent and which solvent is introduced into, released onto

or coated onto the external surface of the enclosure at the time of disposal into a water closet bowl.

5 The present invention also provides a method of disposal of a water disposable enclosure of the second aspect of the invention which includes the step of applying solvent to the enclosure, internally or externally by a spray or other applicator means immediately prior to flushing the enclosure down the water closet.

10 Preferred examples of organic solvent soluble material forming the enclosure include polycaprolactone film and gelatinised starch film, both of which are soluble in the solvent N-methyl pyrrolidone. For this purpose, N-methyl pyrrolidone is a preferred solvent since it is not only very effective but also both biodegradable and non-inflammable.

15 According to a third major aspect of the present invention there is provided a water-dispersible disposable enclosure such as an ostomy pouch or urinary incontinence pouch, which enclosure is formed from a material that will dissolve or otherwise disperse in aqueous media as a result of salt replacement, the salt being applied to the external surface of the enclosure at the time of disposal into a water closet bowl. A particular preferred example of such material and salt are a film of calcium alginate that will dissolve in presence of 20 aqueous sodium salt due to relative solubility of sodium alginate. Therefore, by providing sodium chloride in association with the disposable enclosure formed of calcium alginate, either stored in a pocket or sachet on the enclosure that is ruptured or dissolved at time of disposal or by independently applying the sodium salt to the enclosure at time of disposal, the sodium salt will dissolve in 25 the water of the water closet bowl and replace the calcium of the calcium alginate film to render the enclosure cold water soluble.

30 Where the enclosure is an ostomy pouch it is suitably of the type which has a 2-part attachment to the wearer, having a base portion that semi-permanently mounts around the abdominal opening in the patient and a corresponding flange on the pouch that cooperatively engages with the base portion, the flange being of a substantially rigid construction and in accordance with a further aspect of

the present invention being formed of a rigid grade of the material of any of the previous aspects of the present invention, ie one which is meltable, soluble or dispersible as described herein above, or which is slowly cold-water soluble ie dissolves in cold water over a period of several hours as do certain grades of cold water soluble PVA.

Even where the pouch has a single-piece attachment to the wearer it is conceivable that this might also be made of the said meltable, soluble or dispersible material.

As a further improvement to the design of water-dispersible disposable enclosure of any of the previous aspects of the present invention, the enclosure is suitably at least partially formed of a material and in a configuration whereby exposure to the large volumes of water of a toilet bowl causes differential shrinkage from one region of the enclosure to another thereby tearing the enclosure apart. This may be achieved by, for example, use of strands of polyvinyl alcohol overlain upon or encased within and bonded to a base material which upon sufficient exposure of the strands to water causes shrinkage of the strands, thereby pulling the base material to which the strands are bonded apart. The strands may be formed into a matrix or a matrix may be formed that isn't strictly composed of independent strands but which nonetheless has the effect of tearing the base material and itself apart upon exposure to water.

#### Brief Description of the Drawings

Preferred embodiments of the present invention will now be more particularly described, by way of example, with reference to the accompanying drawings, wherein:

Figure 1 is a front elevation view of an ostomy pouch coated with a water-activated exothermic reagent of the first aspect of the present invention;

Figure 2 is a transverse sectional view through the membrane that forms the pouch of Figure 1;

Figures 3 and 4 are front elevation views of pouches similar to that illustrated in Figure 1 but respectively having a valve-gated reservoir or a sachet holding reagent for melting, dissolving, dispersing or otherwise disintegrating the pouch;

- 5      Figure 5 is a transverse sectional view similar to that of Figure 2 but through a woven or non-woven fabric such as viscose or cotton bonded with hot water soluble material on the internal face of the fabric; and

Figure 6 is a front elevation view of an ostomy pouch having a two part attachment to the wearer.

10      Description of the Preferred Embodiment

Referring to Figures 1 and 2, there is shown an ostomy pouch of broadly conventional shape and having a conventional circular rimmed aperture 1 that is adapted to be adhered to the abdominal opening of an ostomy patient for the passage of fluids from the patient's abdomen into the pouch.

- 15      Illustrated patterning 2 on the external surface of the pouch depicts an external coating 2 of a water-activated exothermic reagent covering the material 3 forming the pouch.

- 20      By way of example, the preferred pouch forming material 3 comprises a hot water soluble polyvinyl alcohol. Suitable specific examples of such polyvinyl alcohol include Vinyon 30 micron from Nippon Goshei which dissolves or disperses at 80°C; HiSelon Type H at 40 micron from the same company which dissolves or disperses at 60°C; and Aquafilm Type A127 at 50 micron from Aquafilm which dissolves or disperses at 60°C. All three of these polyvinyl alcohol materials have been used as the pouch-forming material 3 and when
- 25      coated with a water-sensitive exothermic reagent such as aluminium chloride, calcium chloride or silica gel in small amounts sufficient to raise the localised temperature around the surface of the bag to the temperature levels for dissolution or dispersion of the material on contact with water effectively completely dissolved or dispersed the material within 2 minutes.



In this embodiment it may be desirable to use a comfort panel between the rear face of the pouch and the skin of the wearer or to ensure that the exothermic reagent coating 2 is applied only to the front face of the pouch away from the wearer. Such panel may be formed of, for example, a woven fabric of viscose  
5 or cotton bonded together by a water dispersible polyvinyl alcohol.

By way of further refinement, a protective panel may be provided to extend over the front face of the pouch to protect it from accidental exposure to substantial volumes of water during use. In this case, such a protective panel is perhaps most usefully mounted to the less frequently disposed of base portion 4  
10 of a two part attachment pouch, such as illustrated in Figure 6.

The two part attachment in the Figure 6 embodiment comprises the base portion 4 that adheres over the abdominal opening in the patient and a corresponding annular flange 5 that cooperatively engages with the base portion 4 to mount the pouch in fluid communication with the opening in the patient. The annular rim  
15 of the base portion 5 and the annular flange 4 of the pouch are conventionally formed of materials that are not ideally suited to flushing and that although in some cases may be softenable in contact with water generally retain their rigidity and are non-dispersible. One common material used in the prior art is keraya gum for the one part design and polyethylene or polypropylene for the  
20 two part design.

In accordance with one particular preferred embodiment of the present invention, the annular rim on that base portion and the annular flange on the pouch are suitably both formed of a water soluble dispersible material that may, for example, be a rigid grade of the material 3 used to form the pouch itself or  
25 may be a slowly cold water soluble material such a substantially rigid grade of cold water soluble polyvinyl alcohol. An example of such a polyvinyl alcohol is Ecomaty AX2000 from Nippon Goshei. As an alternative possibility, the flange and annular rim may also be formed from Mater Bi resin modified to dissolve slowly.

30 Turning to the second aspect of the present invention, to be rapidly dispersible for flushing, the pouch may be formed of a material 3 that is rapidly soluble in

relatively small volumes of organic solvent that may be spray applied or otherwise released into or onto the pouch at time of disposal. Examples of such pouch material 3 include 30 micron gelatinised starch film known as Mater Bi which will dissolve well within 2 minutes when combined with the solvent N  
5 Methylpyrrolodine. A further example of pouch forming material rapidly soluble in organic solvent is a film of polycaprolactone that is rapidly soluble in, for example, toluene.

Figures 3 and 4 illustrate different means for associating the solvent with the pouch. In Figure 3 the valve 6 is provided extending into the internal cavity of  
10 the pouch to enable solvent to be introduced into the pouch at time of disposal by means of a pressurised spray or pump-action device.

In Figure 4 a sachet 7 is provided in the wall of the pouch containing solvent that may be released upon puncturing or rupturing the sachet 7 by action of a tool or force.

15 Although described above with respect to a preferred arrangement in which the pouch forming material is a single film of material such as polyvinyl alcohol, the pouch forming material may comprise a composite 9 of, for example, a woven fabric of viscose, cotton or other suitably biodegradable material that is bound together by the hot water soluble material or organic solvent soluble  
20 material 10 on its inner face or, in accordance with the third aspect of the present invention, bound together by a water soluble/dispersible material that only becomes water soluble/dispersible upon salt replacement.

By way of example of this latter aspect of the invention, the pouch is formed of or bound together by calcium alginate that is brought into contact with the water  
25 soluble sodium salt at time of disposal.

In the case of the application of a coating of water-activated exothermic reagent to hot water soluble pouch forming material, the reagent coating need not be applied continuously over the external surface of the pouch but may be laid in a grid pattern or otherwise applied so that the pouch will at least disintegrate into

small enough pieces to be readily flushable. This may be satisfactory, particularly bearing in mind that the materials are generally fully biodegradable.

5

10

15

Claims

1. A water-dispersible disposable enclosure, such as an ostomy pouch or urinary incontinence pouch, which is adapted for flushing down the bowl of a water closet and is formed of a material that is, at least at the time of disposal  
5 into a water closet bowl, combined with a water-activated exothermic reagent that raises the temperature of the enclosure or the water that comes into contact with the enclosure, prior to or upon placement in the water closet bowl, to a level at which the material melts, dissolves or otherwise disperses for ease of flushing.
- 10 2. An enclosure as claimed in Claim 1, wherein the material of the enclosure is a hot water soluble material such as hot water soluble polyvinyl alcohol.
3. An enclosure as claimed in Claim 1, wherein the enclosure-forming material is low melting point polycaprolactone film.
- 15 4. An enclosure as claimed in Claim 2 or Claim 3, wherein the water-activated exothermic reagent is silica gel, aluminium chloride or calcium chloride.
5. An enclosure as claimed in any preceding Claim, wherein the water-activated exothermic reagent is coated upon the external surface of the enclosure  
20 at the time of manufacture and is applied continuously or discontinuously as necessary to achieve adequate disintegration of the product upon disposal.
6. An enclosure as claimed in Claim 5, wherein the reagent is applied substantially solely to the face of the pouch/enclosure that is remote from the wearer, rather than adjacent to the skin of the wearer.
- 25 7. A water-dispersible disposable enclosure, such as an ostomy pouch or urinary incontinence pouch, which enclosure is formed from a material that is rapidly soluble in an organic solvent and which solvent is introduced into,

released onto or coated onto the external surface of the enclosure at the time of disposal into a water closet bowl.

5 8. A method of disposal of a water-dispersible disposable enclosure of the type as claimed in Claim 7, which includes the step of applying solvent to the enclosure, internally or externally by a spray or other applicator means immediately prior to flushing the enclosure down the water closet.

9. An enclosure as claimed in Claim 7, wherein the organic solvent soluble material forming the enclosure is a polycaprolactone film or gelatinised starch film and the solvent is N-methyl pyrrolidone.

10 10. A water-dispersible disposable enclosure, such as an ostomy pouch or urinary incontinence pouch, which enclosure is formed from a material that will dissolve or otherwise disperse in aqueous media as a result of salt replacement, the salt being applied to the enclosure at the time of disposal into a water closet bowl.

15 11. An enclosure as claimed in Claim 10, wherein the enclosure-forming material is a film of calcium alginate and the salt is a sodium salt.

20 12. An enclosure as claimed in any of Claims 1 to 7 or 9 to 11, which comprises an ostomy pouch that has a two-part attachment to the wearer of which at least the flange portion on the pouch that cooperatively engages with a base portion adhered to the wearer is of substantially rigid construction and is formed of a rigid grade of the material of any of the enclosure-forming materials of Claims 1 to 7 or 9 to 11 or which is slowly cold-water soluble, ie dissolves in cold water over a period of several hours.

25 13. A water-dispersible disposable enclosure as claimed in any of Claims 1 to 7 or 10 to 12 which is further characterised in that the enclosure is adapted to tear itself apart by shrinkage of parts of the enclosure upon contact with water.




Fig. 1




Fig. 2




Fig. 3






Fig. 4



# INTERNATIONAL SEARCH REPORT

International Application No  
PCT/GB 96/01267

<b>A. CLASSIFICATION OF SUBJECT MATTER</b> IPC 6 A61F5/445		
According to International Patent Classification (IPC) or to both national classification and IPC		
<b>B. FIELDS SEARCHED</b> Minimum documentation searched (classification system followed by classification symbols) IPC 6 A61F A61L		
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched		
Electronic data base consulted during the international search (name of data base and, where practical, search terms used)		
<b>C. DOCUMENTS CONSIDERED TO BE RELEVANT</b>		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP,A,0 272 816 (SQUIBB & SONS INC) 29 June 1988 see page 3, line 7 - line 11 see page 3, line 50 - page 4, line 21 see page 7, line 26 - line 56 ---	1-13
A	GB,A,2 195 919 (SMITHS INDUSTRIES PLC) 20 April 1988 cited in the application see abstract; figures ---	1,7,8,10
A	GB,A,2 267 711 (ISOLYSER CO) 15 December 1993 see abstract ---	1
A	WO,A,95 08440 (DOW CHEMICAL CO) 30 March 1995 see abstract ---	1
-/-		
<input checked="" type="checkbox"/> Further documents are listed in the continuation of box C. <span style="margin-left: 100px;"><input checked="" type="checkbox"/> Patent family members are listed in annex.</span>		
* Special categories of cited documents : <div style="display: flex; justify-content: space-between;"> <div style="width: 45%;"> <p>*A* document defining the general state of the art which is not considered to be of particular relevance</p> <p>*E* earlier document but published on or after the international filing date</p> <p>*L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</p> <p>*O* document referring to an oral disclosure, use, exhibition or other means</p> <p>*P* document published prior to the international filing date but later than the priority date claimed</p> </div> <div style="width: 45%;"> <p>*T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</p> <p>*X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone</p> <p>*Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.</p> <p>*&amp;* document member of the same patent family</p> </div> </div>		
Date of the actual completion of the international search  <div style="text-align: center; font-weight: bold;">23 September 1996</div>		Date of mailing of the international search report  <div style="text-align: center; font-weight: bold;">03.10.1996</div>
Name and mailing address of the ISA European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+ 31-70) 340-2040, Tx. 31 651 epo nl, Fax: (+ 31-70) 340-3016		Authorized officer  <div style="text-align: center; font-weight: bold;">Sánchez y Sánchez, J</div>



# INTERNATIONAL SEARCH REPORT

Inter. Appl. Application No  
PCT/GB 96/01267

C(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US,A,3 762 454 (WILKINS R) 2 October 1973 see abstract	1
A	EP,A,0 388 924 (SQUIBB & SONS INC) 26 September 1990	

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/GB 96/01267

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP-A-0272816	29-06-88	US-A- 4762738	09-08-88
		AU-B- 646235	17-02-94
		AU-A- 6929991	28-03-91
		AU-B- 611654	20-06-91
		AU-A- 8124787	23-06-88
		CA-A- 1287282	06-08-91
		EP-A- 0726068	14-08-96
		JP-A- 63181758	26-07-88
		US-A- 4830187	16-05-89
		US-A- 4930942	05-06-90
		ZA-A- 8708481	09-05-88
-----			
GB-A-2195919	20-04-88	DE-A- 3727744	17-03-88
		FR-A- 2603189	04-03-88
		JP-B- 7057230	21-06-95
		JP-A- 63063456	19-03-88
		US-A- 4868024	19-09-89
-----			
GB-A-2267711	15-12-93	NONE	
-----			
WO-A-9508440	30-03-95	US-A- 5468526	21-11-95
		AU-A- 7639794	10-04-95
		EP-A- 0720531	10-07-96
-----			
US-A-3762454	02-10-73	NONE	
-----			
EP-A-0388924	26-09-90	US-A- 5009648	23-04-91
		CA-A- 2012010	22-09-90
		JP-A- 2280748	16-11-90
-----			